

Package: IgorR (via r-universe)

August 29, 2024

Type Package

Title Read Binary Files Saved by 'Igor Pro' (Including 'Neuromatic' Data)

Version 0.9.0

Description Provides function to read data from the 'Igor Pro' data analysis program by 'Wavemetrics'. The data formats supported are 'Igor' packed experiment format ('pxp') and 'Igor' binary wave ('ibw'). See: <<https://www.wavemetrics.com/>> for details. Also includes functions to load special 'pxp' files produced by the 'Igor Pro' 'Neuromatic' and 'Nclamp' packages for recording and analysing neuronal data. See <<https://github.com/SilverLabUCL/NeuroMatic>> for details.

Imports bitops, tools, timechange

Suggests spelling, testthat

License GPL (>= 2)

LazyLoad yes

RoxygenNote 7.3.2

Language en-GB

Encoding UTF-8

URL <https://github.com/jefferis/IgorR>,
<https://jefferis.github.io/IgorR/>

BugReports <https://github.com/jefferis/IgorR/issues>

Repository <https://jefferis.r-universe.dev>

RemoteUrl <https://github.com/jefferis/igorr>

RemoteRef HEAD

RemoteSha e989d1fbdd72524d5e4b3848eee7faefe09cde52

Contents

IgorR-package	2
IgorR-private	3
read.ibw	3
read.pxp	4
ReadAllNclampLogTables	6
ReadNclampLogTable	7
SummariseSweepFile	7
SweepFilesToDataFrame	8
tsp.igorwave	9
UpdateSweepDataFrame	9
WaveToTimeSeries	10

Index	11
--------------	-----------

IgorR-package	<i>Read binary files saved by Igor Pro (including Neuromatic data)</i>
---------------	--

Description

This package provides function to read data from the Igor Pro data analysis program by Wavemetrics. The data formats supported are Igor packed experiment format (.pxp) and Igor binary wave (.ibw). See: <https://www.wavemetrics.com/> for details.

Details

It also includes some functions to load special pxp files produced by the Neuromatic/Nclamp packages for recording and analysing neuronal #data. See <https://github.com/SilverLabUCL/NeuroMatic> for details.

Key functions in the package include [read.ibw](#), [read.pxp](#).

Author(s)

Maintainer: Gregory Jefferis <jefferis@gmail.com> ([ORCID](#))

Other contributors:

- Thomas Braun [contributor]

See Also

Useful links:

- <https://github.com/jefferis/IgorR>
- <https://jefferis.github.io/IgorR/>
- Report bugs at <https://github.com/jefferis/IgorR/issues>

IgorR-private

Private functions in IgorR Package

Description

.ReadPackedHeader reads the short record header from the current location in a PXP file

Usage

```
.ReadPackedHeader(con, endian)
```

Arguments

con	an R connection to the file we are reading
endian	either little or big

Details

Note that the recordType will be one of the constants from Igor's enum PackedFileRecordType

Value

a list containing information about the current record

Author(s)

jefferis

read.ibw

Read binary files in the Igor Binary Wave format (IBW)

Description

Read binary files in the Igor Binary Wave format (IBW)

Usage

```
read.ibw(  
  wavefile,  
  Verbose = FALSE,  
  ReturnTimeSeries = FALSE,  
  MakeWave = FALSE,  
  HeaderOnly = FALSE  
)
```

Arguments

wavefile	either a character vector containing the path to a file or an R connection .
Verbose	if TRUE, print status information while reading the file.
ReturnTimeSeries	if TRUE, return as an R time series (package ts).
MakeWave	if TRUE, assign wave to a list in the global user environment.
HeaderOnly	if TRUE, only return the header of the Igor Wave.

Value

A vector containing the wave data or, if MakeWave == TRUE, returns the name of a new R vector containing the data which has been made in the user environment

Author(s)

jefferis

See Also

Other igor-io: [WaveToTimeSeries\(\)](#), [read.pxp\(\)](#)

Examples

```
# return a list containing the wave
wavedata=read.ibw(system.file("igor", "version5.ibw", package="IgorR"))
sum(wavedata)

# make a list containing the wave's data in the users's environment
wavename=read.ibw(system.file("igor", "version5.ibw", package="IgorR"), MakeWave=TRUE)
sum(get(wavename))
```

read.pxp

Reads an Igor Pro Packed Experiment (.pxp) file

Description

Note that PXP files are only partially documented so some contents cannot be parsed (e.g. image data). This function currently reads data records (Igor waves and variables), history, procedures, recreation macros and plain text notebooks. Formatted notebooks cannot be read.

Usage

```
read.pxp(
  pxpfile,
  regex,
  ReturnTimeSeries = FALSE,
  Verbose = FALSE,
  StructureOnly = FALSE,
  ExtractText = FALSE,
  IgorPlatform = NULL,
  ...
)
```

Arguments

pxpfile	character vector naming a PXP file or an R connection .
regex	if TRUE, only read records (e.g. waves) in the PXP file whose names match a regex .
ReturnTimeSeries	if TRUE, Igor waves are returned as a <code>link{ts}</code> object with sensible x scaling (FALSE by default).
Verbose	whether to print information to console during loading (numeric values are also allowed 0=none, 1=basic, 2=all).
StructureOnly	(TODO) if TRUE, only the structure of the PXP file for inspection.
ExtractText	whether to extract procedures, recreation macros, history and plain text notebooks (FALSE by default).
IgorPlatform	OS on which Igor file was saved (windows or macintosh).
...	optional parameters passed to read.ibw .

Details

IgorPlatform will determine in which encoding text is read (WINDOWS-1252 for windows and macintosh for macintosh). Unique abbreviations are acceptable. Defaults to "windows" on Windows, "macintosh" otherwise. Note that Igor Pro 5.5 added a PlatformRecord to the PXP file format which is used to determine the file's platform of origin when available. Since this is information straight from the horse's mouth it will override the IgorPlatform argument.

Value

A list containing all the individual waves or variables in the PXP file.

Author(s)

jefferis

See Also

Other igor-io: [WaveToTimeSeries\(\)](#), [read.ibw\(\)](#)

Examples

```
r=read.pxp(system.file("igor","testexpt.pxp",package="IgorR"))
```

ReadAllNclampLogTables

Read all Nclamp log tables from a directory into a list

Description

Read all Nclamp log tables from a directory into a list

Usage

```
ReadAllNclampLogTables(logfiledir, pattern = "_log[0-9]+[.]pxp$", ...)
```

Arguments

logfiledir path to directory containing log files (pxp files).
pattern optional regular expression – see [list.files](#).
... additional parameters for [ReadNclampLogTable](#).

Value

A named list containing one dataframe for each parsed log file.

Author(s)

jefferis

Examples

```
## Not run:  
logfiles <- ReadAllNclampLogTables("/GD/projects/PhysiologyData/logs")  
str(logfiles)  
  
## End(Not run)
```

ReadNclampLogTable *Read the log table produced by Nclamp acquisition software for Igor*

Description

log tables are special Igor .pxp files that contain only variables. Each entry corresponds to a single run of an Nclamp protocol, storing information like protocol name, run time etc.

Usage

```
ReadNclampLogTable(f, Verbose = FALSE)
```

Arguments

f path to the log file.
Verbose whether to print status information while reading the file.

Value

A dataframe containing a row for each acquisition protocol run.

Author(s)

jefferis

SummariseSweepFile *Extract summary information from an Nclamp/Igor Sweep File*

Description

e.g. for import into Physiology database

Usage

```
SummariseSweepFile(f, Verbose = FALSE)
```

Arguments

f path to an Nclamp/Igor PXP format sweep file.
Verbose if TRUE, print details while parsing underlying PXP file.

Value

A list of about 25 fields summarising the sweep file.

Author(s)

jefferis

Examples

```
l <- SummariseSweepFile(system.file("igor", "WedJul407c2_001.pxp", package="IgorR"))
cat("There are", l$NumWaves, "waves in the file each of total duration", l$StimWaveLength,
    "ms and sample duration", l$StimSampleInterval, "ms \n")
```

SweepFilesToDataFrame *Summarise multiple sweep files into a single dataframe*

Description

Note that this is still a little fragile if the lists produced by [SummariseSweepFile](#) do not have consistent field names.

Usage

```
SweepFilesToDataFrame(ff)
```

Arguments

ff paths to a set of sweep files.

Value

A dataframe with rows for each sweep file.

Author(s)

jefferis

See Also[SummariseSweepFile](#)

tsp.igorwave	<i>Return tsp attribute of Igor wave (start, end, frequency)</i>
--------------	--

Description

Note that $end = (npts-1) * deltat$

Usage

```
tsp.igorwave(wave)
```

Arguments

wave	Igor wave loaded by read.ibw or read.pxp
------	--

Value

numeric vector with elements start, end, frequency

Author(s)

jefferis

See Also

[tsp](#)

UpdateSweepDataFrame	<i>Update the CSV file summarising the sweeps in an Nclamp data folder</i>
----------------------	--

Description

Update the CSV file summarising the sweeps in an Nclamp data folder

Usage

```
UpdateSweepDataFrame(  
  folder,  
  outfile = NULL,  
  action = c("update", "force"),  
  DryRun = FALSE  
)
```

Arguments

folder	path to the folder.
outfile	path to outfile (default: /path/to/datafolder/datafolder.csv).
action	update newer (default) or force update (not yet implemented).
DryRun	if TRUE, report which files would be processed, but do nothing.

Value

TRUE if something happened, FALSE otherwise.

Author(s)

jefferis

WaveToTimeSeries	<i>Convert an Igor wave (wave list) loaded by read.ibw into an R time series</i>
------------------	--

Description

Where there are multiple waves, they are assumed to be of compatible lengths so that they can be joined together by cbind.

Usage

```
WaveToTimeSeries(WaveData, ReturnOriginalDataOnError = TRUE)
```

Arguments

WaveData	a wave or list of waves
ReturnOriginalDataOnError	If we can't make a time series, return return original data (default TRUE)

Value

a time series or multi time series ([ts](#), [mts](#))

Author(s)

jefferis

See Also

Other igor-io: [read.ibw\(\)](#), [read.pxp\(\)](#)

Index

- * **igor-io**
 - read.ibw, [3](#)
 - read.pxp, [4](#)
 - WaveToTimeSeries, [10](#)
- * **package**
 - IgorR-package, [2](#)
 - .ReadPackedHeader (IgorR-private), [3](#)
- connection, [4](#), [5](#)
- IgorR (IgorR-package), [2](#)
- IgorR-package, [2](#)
- IgorR-private, [3](#)
- list.files, [6](#)
- read.ibw, [2](#), [3](#), [5](#), [10](#)
- read.pxp, [2](#), [4](#), [4](#), [10](#)
- ReadAllNclampLogTables, [6](#)
- ReadNclampLogTable, [6](#), [7](#)
- regex, [5](#)
- SummariseSweepFile, [7](#), [8](#)
- SweepFilesToDataFrame, [8](#)
- ts, [4](#), [10](#)
- tsp, [9](#)
- tsp.igorwave, [9](#)
- UpdateSweepDataFrame, [9](#)
- WaveToTimeSeries, [4](#), [5](#), [10](#)